

IN THE CLAIMS:

Please amend the claims as follows. This listing of the claims will replace all prior versions, and listings, of claims in the application:

1-9. (canceled)

10. (Currently amended) A plastic container for domestic washing machines which internally receives a rotary drum whose axes are mounted on bearings arranged in a bearing shell made of metallic material,

wherein ~~at least one~~ a plastic member is accommodated on at least one section of [the] a surface of the bearing shell, with the [one] plastic member and the bearing shell together forming a structural unit, before the remainder of the plastic container is injection-molded onto the structural unit formed by the bearing shell and the plastic member.

11. (Canceled)

12. (Currently amended) The plastic container according to claim 10, wherein the material of ~~at least one of the plastic members~~ member differs from the material of the remainder of the plastic container.

13. (Canceled)

14. (Currently amended) The plastic container according to claim 10, wherein the plastic member ~~forms an envelope or bushing for the structural unit formed by~~ covers a portion of an inside surface of the bearing shell and the plastic member.

15 (Currently amended) The plastic container according to claim 14, wherein the ~~envelope or bushing forming the~~ plastic member is formed with a plurality of ribs.

16. (Currently amended) The plastic container according to claim 14, wherein the ~~envelope or bushing forming the~~ plastic member covers [the] an entire [side] outside surface of the bearing shell.

17. (Currently amended) The plastic container according to claim 10, wherein the at least one section of the surface of the bearing shell is a first portion of an outside surface of the bearing shell, the plastic member is a ring which surrounds the at least one section of the surface of the bearing shell, and a second portion of the outside surface of the bearing shell is contacted by the remainder of the plastic container.

18. (Canceled)

19. (Currently amended) A container for a washing machine having a rotary drum disposed within the container and being mounted for rotation with respect to the

container, the container being for retaining liquids during operation of the washing machine, the container comprising:

a bearing shell for receiving at least one bearing, the bearing shell having a substantially cylindrical shape;

a plastic member formed on the bearing shell; and

[the] a container body being formed on the plastic member ~~and retaining liquids during operation of the washing machine.~~

20. (Currently amended) The plastic container according to claim 19, wherein the plastic member includes at least one projection extending into the container body to form an interlocking engagement with the container body.

21. (Currently amended) The plastic container according to claim 19, wherein the plastic member is made from a first plastic material and the container body is made from a second plastic material ~~being~~ different than the first plastic material.

22. (Previously Presented) The plastic container according to claim 21, wherein the first plastic material has higher hardness and strength characteristics than the second plastic material.

23. (Previously Presented) The plastic container according to claim 21, wherein the bearing shell is made from a metal material.

24. (Currently amended) The plastic container according to claim 19, wherein the plastic member is formed directly on the bearing shell with a first injection molding process and the container body is formed directly on the plastic member with a second injection molding process.

25. (Currently amended) A method for making a container for retaining liquids within a washing machine having a rotary drum mounted for rotation with respect to the container, the method comprising the following steps:

providing a bearing shell for receiving at least one bearing, the bearing shell comprised of metallic material;

~~applying~~ forming a plastic member ~~formed~~ on the bearing shell by [an] a first injection molding process, the plastic member and the bearing shell together forming an intermediate structure, [and] the plastic member ~~comprising~~ being a portion of [a] the container ~~which has not yet been completed~~; and

then applying ~~the remainder of the~~ a container body formed on the ~~plastic member~~ intermediate structure by [an] a second injection molding process.

26. (Currently amended) The method according to claim 25, further comprising forming at least one projection extending from the plastic member and into the container body to form an interlocking engagement between the plastic member and the container body.

27. (Currently amended) The method according to claim 25, wherein the plastic member is formed from a first plastic material and the container body is formed from a second plastic material ~~being~~ different than the first plastic material.

28. (Previously Presented) The method according to claim 27, wherein the first plastic material has higher hardness and strength characteristics than the second plastic material.

29. (Currently amended) A method for making a container for retaining liquids within a washing machine having a rotary drum mounted for rotation with respect to the container, the method ~~for making a container~~ comprising:

providing a bearing shell for receiving at least one bearing, the bearing shell comprised of metallic material;

applying a plastic member on the bearing shell via [an] a first injection molding process, the plastic member and the bearing shell together forming an intermediate structure and the plastic member ~~comprising~~ being a portion of [a] the container; and

after the plastic member applied on the bearing shell has at least partially cured following the step of applying the plastic member, forming the remainder of the container on the intermediate structure with [an] a second injection molding process.

30. (Previously Presented) The plastic container according to claim 10, wherein the remainder of the plastic container is injection-molded onto the structural unit formed by the bearing shell and the plastic member only after the plastic member has been applied to the bearing shell by an injection molding process and allowed to at least partially cure.

31. (New) The plastic container according to claim 10, wherein the bearing shell is adapted to receive the bearings after the remainder of the plastic container is injection molded onto the structural unit.

32. (New) The container according to claim 19, wherein the bearing shell is adapted to receive the at least one bearing after the container body is formed on the plastic member.

33. (New) The method according to claim 25, wherein the bearing shell is adapted to receive the at least one bearing after the container body is formed on the plastic member.

34. (New) The method according to claim 29, wherein the bearing shell is adapted to receive the at least one bearing after the remainder of the container is formed on the intermediate structure.